



ISOLMANT FASCIA TAGLIAMURO ISOLGYPSUM

AIRBORNE SOUND | CLADDED WALL INSULATION

ADHESIVE STRIPS FOR A PERFECT ACOUSTIC SYSTEM FOR CLADDED WALLS

WHAT IS ISOLMANT FASCIA TAGLIAMURO ISOLGYPSUM?

5 cm adhesive strips of HD Isolmant polyethylene (approx. 70 kg/m³). Product specific to install pre-coupled plasterboards.

SPECIFIC APPLICATIONS

The use of Isolmant Fascia Tagliamuro IsolGypsum is necessary to separate the resilient cladding (panel pre-coupled with plasterboard) from the underlying structure in order to avoid the phenomenon of a rigid connection between the various building components. Thanks to its calibrated density, Isolmant Fascia Tagliamuro IsolGypsum ensures the necessary mechanical resistance (to avoid cracks in the partitions) and the anti-vibration spring effect required to exclude an acoustic bridge.

ADVANTAGES

- Inalterable in time.
- Unlimited duration.

ISOLMANT Green Planet

- Volatile organic compounds free (VOC A+).



HEALTHY

ISOLMANT FASCIA TAGLIAMURO ISOLGYPSUM TECHNICAL SPECIFICATIONS

NOMINAL THICKNESS:	6 mm
ACOUSTIC INSULATION:	This product improves the acoustic behaviour of the wall
EMISSION OF VOLATILE ORGANIC COMPOUNDS:	VOC A+ ⁽¹⁾
CE MARKING:	Harmonised standards for CE marking are NOT currently available for acoustic insulation products. This means that Isolmant products are currently NOT subject to CE marking, nor to the drawing up of a PDO (declaration of performance) or DDP (declaration of performance). All Isolmant products are placed on the market in compliance with the regulations in force in the country of destination and with the necessary certifications to guarantee their use in dedicated applications.
SIZE:	h 5 cm x 25 m linear strips
PACKAGE:	10 strips equal to 250 linear metres

(1) Istituto Giordano test report no. 3768S1

ITEM SPECIFICATIONS

HD strip (approx. 70 kg/m³) made of HD reticulated expanded closed-cell polyethylene to install pre-coupled plasterboard panels. This product is supplied in 5 cm high strips. Nominal thickness 6 mm.

ISOLMANT FASCIA TAGLIAMURO ISOLGYPSUM INSTALLATION INSTRUCTIONS



1

Before installing your panel, Isolmant Fascia Tagliamuro IsolGypsum must be placed on the ground, against the wall to be covered.

Specifically:

- Install Fascia Tagliamuro IsolGypsum on the screed or the actual flooring by using the tape fabric.
- Directly apply this product on the pre-coupled panel.
- Trim the extra fabric left.



WARNINGS:

*This technical data sheet does not constitute a specification and, if it consists of several pages, please ensure that you have consulted the complete document. Although these instructions are the result of our best expertise they are indicative. The user should establish whether the product is suitable for its intended application. The user will be also in charge of all the responsibility for the use of the product itself.

**The sound insulation values given in this technical data sheet are the result of laboratory tests or tests carried out on site: they cannot be considered a predictive value for every situation that may occur on site. Acoustic performance is closely linked to the specific conditions of each site.

***Caution: do not expose the product to direct sunlight.

isolmant



Via dell'Industria 12, Località Francolino 20074 Carpiano (Mi) Tel. +39 02 9885701 Fax +39 02 98855702
clienti@isolmant.it - www.isolmant.it - www.sistemapavimento.it - www.isolmant4you.it

Isolmant is a TECNASFALTI srl's registered trademark - © TECNASFALTI - All rights reserved - Copying, even partially, is forbidden - In force since November 2020 - This document supersedes and replaces all previous versions.